PLIOSEAL

FLEECE ROOF REPAIR TAPE

Product Overview: PLIOSEAL Fleece Roof Repair Tape is a premium roofing tape laminate consisting of synthetic polymer adhesive backed by a high-strength, stitch bonded fleece facer. This product is formulated to provide optimum levels of tack, shear strength and possesses excellent heat, water, and chemical resistance.

Product Uses: PLIOSEAL Fleece Roof Repair Tape is designed specifically for use in the roofing industry. It is commonly used to cover standing seams, joints, flashings, fasteners and dissimilar surfaces on metal roofs and decks prior to the application of acrylic and elastomeric roof coatings.

Technical Information:

Raw Material Base	Synthetic Polymer	Adhesive Strength (ASTM D330)	9.8 pli
Physical State	Solid	Elongation, Adhesive (ASTM D412)	>500%
Manufactured State	Extruded Roll	Specific Gravity, Adhesive	1.40 – 1.50
Color (Fleece)	White	Self Sealability (ASTM D1970)	Pass
Odor	Odorless	Application Temperature	-20°F – 150°F
Solids Content	100%	Shelf Life	24 Months

Application Information: All involved surfaces should be clean and dry. PLIOSEAL Fleece Roof Repair Tape is extruded onto release paper backing to facilitate handling. For most efficient usage, remove the release paper from the adhesive when preparing for use and handle only the fleece facer. Firmly press the material into place to ensure proper adhesion. Ensure that the application is free of contaminants and air entrapment. If involved surfaces are greasy, wipe with a light application of mineral spirits prior to installing PLIOSEAL Fleece Roof Repair Tape.

Packaging & Handling: PLIOSEAL Fleece Roof Repair Tape is sold in rolls that are fifty feet in length and available in 2, 3, 4, 6, 8, and 12 inch widths. No special handling is required for this product, though storage in a cool, dry area is recommended for maximum shelf life and effectiveness. Tools and equipment used while applying PLIOSEAL Fleece Roof Repair Tape can be cleaned using mineral spirits, if necessary.

Safety Instructions: No special requirements are needed. An SDS is available upon request.

Contact Us: For more information regarding this product and others, please contact us at:

Edge Adhesives
3709 Grove City Road
Grove City, OH 43123

Phone: 1-614-875-6343
Email: info@edgeadhesives.com
www.edgeadhesives.co

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Edge Adhesives control are such that Edge Adhesives assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.